



Tolerance Table		
Dimensions Range	Metal/Plastic	Cable Length
>0~10	± 0.1	± 0.5
>10~25	± 0.15	± 1.0
>25~50	± 0.2	± 2.0
>50~100	± 0.3	± 5.0
>100~250	± 0.5	± 8.0
>250~500	± 0.6	± 10.0
>500	± 0.8	± 15.0
Angel	± 0.5°	
In drawing"⌀↗" shown are important control dimensions; All material must comply with "ROHS" & "REACH" requirements.		

ITEM NO.	PART OR IDENTIFYING NO.	NOMENCLATURE OR DESCRIPTION	MATERIAL SPECIFICATION	QTY REQD
PARTS LIST				
THIS DOCUMENT CONTAIN INFORMATION PROPRIETARY TO TRAXON TECHNOLOGIES LTD. USE OR DISCLOSURE WITHOUT WRITTEN PERMISSION BY TRAXON IS EXPRESSLY FORBIDDEN.			Our Brand traxonOSRAM	
UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MM. AND TOLERANCES ARE: FRACTIONS DECIMALS ANGLES Refer to ISO 2768-m			MODEL AL Dot XS	
MATERIAL See Notes			PART DESCRIPTION AL DO XS LEAD CABLE 3.5M	
FINISH See Notes			SIZE A3	
3RD ANGLE PROJECTION			IC Code.: AM461760055	
QUAL ENG			REV. A	
SCALE			CAD FILE:	
SHEET 1 OF 1			CONFIDENTIAL	